


Edit pavement schedule information on this detail to ensure pavement schedule meets the NCDOT 2018 Superpave manual requirements unless exception is granted by the City.

SURFACE COURSE
1.5 TO 2.25" S 9.5X
INTERMEDIATE COURSE
2.25 TO 4.0" I 19.0X
BASE COURSE
3.0 TO 5.5" B 25.0X

NOTES:

1. NEW PAVEMENT SHALL HAVE SECTION THICKNESS DESIGNED TO NCDOT SUPERPAVE STANDARDS AS PROVIDED BY ENGINEER OR MATCH EXISTING CONSTRUCTION, WHICH EVER IS GREATER OR AS SPECIFIED BY THE CONTRACT DOCUMENTS.
2. TRENCH IS TO BE BACKFILLED IN COMPACTED 6" LAYERS BEFORE PAVEMENT REPAIRS ARE MADE.
3. REFER TO EARTHWORK SPECIFICATIONS FOR EMBEDMENT AND FILL REQUIREMENTS.
4. THIS DETAIL SHOWS ASPHALT PAVEMENT REPLACEMENT. THE WIDTH OF PAY LIMITS SHALL APPLY TO STONE AND CONCRETE PAVEMENT AS WELL.
5. 18" MIN. AROUND PATCHES AND 36" MIN. AT CURB CUTS.

UTILITY CUT REPLACEMENT DETAIL
SCALE: NONE

				CITY OF CONCORD STANDARD DETAIL UTILITY CUT REPLACEMENT		
No.	Date	By	REVISION			
Drawn By:	Checked By:	Approved By:	Date	Sht	of	
SVM	MSH		11/01	1	1	